



## POLI HT 16<sup>(5/8")</sup>- -19<sup>(3/4")</sup>

### PNEUMATIC STRAPPING TOOL WITH FRICTION WELD SEAL FOR PLASTIC PET STRAP — FLAT AND ROUND SURFACES

#### TECHNICAL DATA / APPLICATIONS :

Powerfull, compact and easy to use strapping tool to use in heavy duty industrial applications especially with high quality PET Polyester strapping. Available standard in two strap sizes:16mm (5/8") and 19mm(3/4").

Package type	Flat, Round surface (min.Diam. 700mm– 28")
Strap quality	PET
Strap width	From 16mm up to 19mm (5/8"- 3/4")
Strap thickness	From 0,8mm up to 1.27mm ( 0.031" - 0.05")
Max. Tension	4000N (16mm) - 5000N (19 mm)
Air pressure and consumption	From 5,5 up to 6,5 bar MAX / 12 l/s (14 l/s welding )
Max. Tension speed	Around 6 mt/min
Joint type	Friction weld seal
Weight	Around 5,3 Kg
Order code Poli HT16	110.160.630
Order code Poli HT19	110.190.630

- ERGONOMIC
- MODERN DESIGN
- COMPACT AND LIGHT
- NEW BOSCH MOTORS
- INSERT BOTH STRAPS TOGETHER
- EASY TO REMOVE THE TOOL



- HIGH TENSION ON STRAP
- NEW LOCK TENSION STRAP
- ON REQUEST UPPER AIR CONNECTION CONFIGURATION

SIAT S.p.A. Via Puecher, 22 - 22078 Turate (CO) Italy • Tel +39.02.964951 • Fax +39.02.9689727

[www.siat.com](http://www.siat.com) • [www.columblatools.it](http://www.columblatools.it) • [www.maillis.gr](http://www.maillis.gr) • [siat@siat.com](mailto:siat@siat.com)